

SPECIFICATION



PRESTO 238 Panel Printer**CPI Product number:**

012 142 051 01

Operating field:

Public transport

Electronic Cash

Industrial

Self servicing machine

Parking

Gambling

Applications:

Receipt- Printer

Ticket- Printer

Protocol- Printer

Kiosk- Printer

Specifications**General:**

Emulation	Driver in Bit- Image Mode for Windows 2000, XP, Linux CUPS or ASCII Mode with ESC/FS Commands
Printing method	Non impact line Direct thermal sensitive
Resolution	203 dpi
Print speed	max. 200 mm/sec
Print width	72/80 mm
Interfaces	USB Full Speed, RS232 (115 KB)
Control panel	Display: Status LED

Paper management:

Paper width	80 mm
Paper length	no limit
Paper weight	60 – 100 gr/qm
Paper stock	Roll
Diameter roll	max. 70 mm
Paper Typ	Direct thermal paper
Paper length	no Limit or format length
Paper cutting	partial cut
Sensorik	complete monitoring of the paper path. PVE, PE
Lifetime print- head	at least 100 Km of printed Lines
Lifetime Cutter	0,5 million cuts
Power supply	24V DC
Current consumption	stand by: 0,15 A typical: 1,2 A peak: 3,5 A
Operating temperature	-20 – +70° Celsius (no condensation)
Operating humidity	-20 - +85° Celsius (no condensation)
Dimensions (W*D*H)	xx*150*125 mm
Weight	

ASCII Mode:

Print direction	Portrait/Landscape/Upside down
Fonts/CodePages	numbers of n Character dependent on free Memory
Standard Font 203dpi	CodePage 437 in Arial 20, 16, 14, 12 and 10 *22 Dots available: 437, 737, 850, 852, 857, 860, 866, 869, 1252, 1253, 1254
Character addressing	1Byte CodePage 2Byte Unicode
Character modification	Enlarge, emphasise, underline, Reverse, italic, sub- superscript
Label graphics or text	numbers of n Label dependent on free Memory
Memory	448 KB Flash fore Fonts, Logo and Download Character
Barcodes	Code 2 of 5, Codabar, Code 39, Code 128, EAN-8/13/128, UPCA/E

Tools:

Label	Creating a download graphic- Logo's
-------	-------------------------------------